

Transparent hose with white spiral

Temperature range

-20° C - +50° C

Features

Plasticized PVC hoses with spiral reinforcement of anti-shock rigid PVC. Smooth inside surface, outside corrugated. Flexible with an high mechanical resistance. Resistant to atmospherical agents and to most chemicals.



Applications

Very flexible vacuum hose, for industries, domestic vacuum cleaners, aerating and conditioning plants and suction of fumes, gas, etc.

Internal diameter [mm]	Weight [g/m]	Wall thickness [mm]	Wall thickness [mm]	Bend radius [mm]	Vacuum [m/H2O]	Package [m]	Package Size [m3]
20	100	2,2	0,5	40	4	30	0,040
25	105	2,2	0,5	40	3	30	0,050
30	140	2,4	0,5	40	3	30	0,062
32	140	2,4	0,5	40	3	30	0,065
35	170	2,4	0,5	40	3	30	0,098
38	195	2,5	0,5	50	3	30	0,124
40	200	2,6	0,5	60	3	30	0,124
45	245	2,6	0,5	80	2,5	30	0,142
50	290	3,0	0,5	90	2,5	30	0,182
55	360	3,0	0,5	90	2,5	30	0,195
60	425	3,3	0,8	100	2,5	30	0,279
63	460	3,3	0,8	100	2,5	30	0,279
70	500	3,3	0,8	110	2,5	30	0,312
76	550	3,4	0,8	110	2,5	30	0,343
80	590	3,6	0,8	130	2,5	30	0,375
90	670	4,2	0,8	150	2	30	0,529
100	750	4,3	0,8	160	2	30	0,627
110	900	4,5	1,0	190	2	30	0,746
120	1000	4,8	1,0	200	2	30	0,855
127	1100	5,0	1,0	230	2	30	0,923
130	1200	5,0	1,0	250	2	30	0,984
140	1300	5,2	1,0	260	2	30	1,070
150	1500	5,4	1,0	270	2	20	0,928
160	1670	6,0	1,0	280	1	20	1,078
170	1750	6,0	1,0	285	1	20	1,200
180	1850	6,0	1,0	450	1	20	1,283
200	2200	6,0	1,2	600	1	10	1,513