


CALORSTEAM /AL FDA 170°C

TEXTILE REINFORCEMENT STEAM HOSE 7 BAR - FDA





APPLICATION

Delivery hose for potable hot water mixed with steam and detergents. Mainly used for washdown and sterilization in the food industry workshops

TUBE

White, smooth, food quality EPM rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Blue, smooth, cloth impression $\ensuremath{\mathbf{EPDM}}$ rubber compound, abrasion, ozone and weather resistant

WORKING TEMPERATURE

-40°F +338°F

SPECIFICATIONS

FDA title 21, art.177.2600 for aqueous foods

| | | | | 4 | | | | | 21 22 23 |
|----|-------|----|---------|--------|-----|-----|-----|------|-------------|
| ID | | 0D | | WEIGHT | WP | | BP | | COIL LENGTH |
| mm | inch | mm | inch | kg/m | bar | psi | bar | psi | m |
| 10 | 13/32 | 20 | 25/32 | 0.28 | 7 | 105 | 70 | 1050 | 40 |
| 13 | 1/2 | 23 | 29/32 | 0.37 | 7 | 105 | 70 | 1050 | 40 |
| 15 | 19/32 | 25 | 1 | 0.41 | 7 | 105 | 70 | 1050 | 40 |
| 16 | 5/8 | 26 | 1 5/16 | 0.43 | 7 | 105 | 70 | 1050 | 40 |
| 19 | 3/4 | 31 | 1 7/32 | 0.58 | 7 | 105 | 70 | 1050 | 40 |
| 25 | 1 | 37 | 1 29/64 | 0.75 | 7 | 105 | 70 | 1050 | 40 |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

| ■ CALORSTEAM | B W.P. 7 BAR | AL-FOA 1701G | ихи 📳 ізда доліта ізапо | |
|----------------------|----------------|--------------|-------------------------|--|
| TGT CALORSTEAM | W.P. 7 BAR FDA | ITALY | tubi gomma torino | |